



# RowCrop™ Spreader

AND OPEN FIELD

8 Ton Lime and 8 Ton Fertilizer Capacity



Picture shows optional equipment

## Your choice of wheel track between 72" and 120"

More versatile  
Legendary reliability  
Tougher than ever

The RC-8 ton Row Crop Spreader Series is designed for growers who need wide swath spreading of lime and fertilizer, and want the ability to top-dress on standing crops. The bolt on Easy Swap™ axle can be swapped out to provide new wheel spacing should your row width change in the future. All RC spreaders come standard with Cor-Ten HSLA weathering steel hoppers.

The RC-8010 is designed for spreading damp stockpiled lime. The steep 53 degree side slopes and 4" drop pan combination prevent bridging. It will also spread fertilizer, compost, litter and more.

The larger volume RC-8012 is designed for 8 tons of fertilizer while maintaining the ability to spread other materials.

### Standard features

- Your choice of wheel track between 72" and 120" to match your row spacing
- Easy Swap™ axle can be switched out for different wheel tracks to future proof the machine against crop spacing changes
- Unibody, fully welded design to resist torsional stresses prolonging the life of the spreader
- Convenient electronic actuator allows for gate height adjustments from your tractor seat
- Sized right for either damp lime (RC- 8010) or fertilizer (RC-8012) capacities
- Top-driven, dual hydraulic spinners keep the motors out of the product flow for longer trouble free life
- Stoltzfus' standard 24" wide conveyor for multi-material use. The RC- 8010's 53° hopper side slopes prevent bridging for wet lime, and the RC-8012's 45° degree side slopes offer larger capacity perfect for lighter flowable materials.
- Cor-Ten HSLA steel hopper for longer life
- Spreads lime up to 7,000 lbs/acre and fertilizer down to 125 lbs/acre

"I bought my spreader 2 years ago for lime and fertilizer. It does a great job. I'm very pleased. It runs perfectly, no issues."

— Michael, Campbell, NY



# Discover the Stoltzfus Difference



The Stoltzfus Row Crop spreaders come standard with the Easy Swap™ axle. Choose your wheel track when ordering. Swap in a new one if your needs ever change.

Upgrade to Variable Rate Technology for better utilization of valuable nutrient inputs.



Electronic actuator to open and close the metering gate from the comfort of your seat



Special Sawtooth Delivery™ feature for low rates of fertilizer still handles damp ag lime with ease



Spinner motors are mounted out of the flow of corrosive materials for increased life



Steep, 53° hopper side slopes eliminates damp lime bridging on the RC-8010 and 45° side slopes on the RC- 8012 allow higher capacity for fertilizer and other more flowable materials



Unibody, fully welded design resists torsional stresses and prolongs the life of the spreader

## Popular options

- Spare axles (specify wheel track)
- PTO-Hydraulic upgrade
- Variable Rate Ready (compatible with your Raven controller)
- Corner pockets (for sideboards)
- Lights
- Roll top tarp
- 304 Stainless steel hopper
- Shredder (breaks up large clumps before they hit the spinners)
- Flotation tires



Shredder to chop up clumps and give a smoother flow of material onto the spinners



Self-contained PTO hydraulics reduces the strain on your tractor's hydraulic system

## RC-8010 /8012 ROW CROP SPREADER SPECIFICATIONS

Models	8010	8012	Models	8010	8012
<b>Max. load</b>	8 tons	8 tons	<b>Overall length</b>	19.5 ft.	21.5 ft.
<b>Hopper volume</b>	177 cu.ft.	331 cu.ft.	<b>Overall width</b>	87-136 in.	102-136in.
<b>Hopper volume</b>	142 bu.	267 bu.	<b>Overall height</b>	106 in.	115 in.
<b>Hopper length</b>	10 ft.	12 ft.	<b>Wheel track</b>	72-120 in.	
<b>Hopper width</b>	78 in.	102 in.	<b>Standard tires</b>	380/90R46	
<b>Hopper depth</b>	45 in.	59 in.	<b>Weight</b>	5,800 lbs.	6200 lbs.



**STOLTZFUS**  
Spreaders

**1-800-843-8731**

StoltzfusSpreaders.com  
Morgantown, PA 19543

Dealer information: