

Lime Spreaders WLS 2, 4, 5, 8 and 10 Ton Models



Spread it yourself and save

Stockpiled Ag Lime (wet or damp) Gypsum Marl Fertilizer Compost





Discover the Stoltzfus Difference

The original wet (damp or stockpiled) lime spreader designed for years of heavy use

For farmers who are dissatisfied with light duty spreaders, the Wet Lime Spreader (WLS) is a machine that is built for spreading wet or damp agricultural lime. Unlike a fertilizer spreader, the Wet Lime Spreader has a 24 inch wide conveyor and steep, 53 degree side slopes to prevent material bridging in the hopper.

The lime pile does not need to be kept dry, and can sit in the corner of your field for months until needed. The lime can then be spread when conditions are right instead of waiting in line for the custom applicator to come around.

Standard features

- **2**, 4, 5, 8 and 10 ton capacities
- Orchard/Vineyard configurations
- Fertilizer kit for rates down to 125 lbs/acre
- Sawtooth Delivery[™] feature
- Walking beam suspension (Spring suspension on 2 ton)
- Top driven spinners
- Fill-for-life heavy duty gear box (2-8 ton) and heavy duty PTT Hydraulics (10 ton)

- Unibody, fully welded design
- Structural steel frame
- Extra body braces
- 7 gauge steel pan
- 53-degree body sides
- 24" slat style chain
- Telescoping chain tighteners
- Self-alignment idler shaft
- Carbon-steel construction
- Inverted "V" center cover



Ingenious engineering

Our testing found that sides with a 53° slope provide the best combination of material flow and capacity, and our 4" vertical pan design eliminates bridging.



Unibody construction

Wet Lime Spreaders are actually one solid weldment. That's what makes them so strong. Even the supporting ribs are welded every inch where they attach to the body.



Difference in the details

For example, placing the spinner gearboxes or hydraulic motors above the material flow reduces exposure to corrosive materials. Furthermore, it eliminates vibration and isolates the gearbox from the shock of material pounding on the spinner disk. "My spreader is 30 years old and still spreading. It's a long lasting spreader, built rugged. I love the spread pattern. Good parts service."

- Richard, Darlington, MD

"You can easily run 100 tons through a day. I bought it 25 years ago and it has saved me a lot of money." - Merv, Union City, PA

"The best piece of equipment I ever bought. 33 years old. It went through a barn fire and it spreads like the day we bought it." - Tom, Henderson, MD



The WLS Spreader spreads:

- Stockpiled Ag Lime (wet or damp)
- Beet lime
- Gypsum
- Marl
- Fertilizer
- Compost
- Poultry manure

- Sand
- Crushed shells
- Cement plant
 - stack dust
- Wood shavings
- Dirt
- Cover Crops
 - (blended w/fertilizer)

■ Grape hulls

Ask us about your most challenging material.



Smoother material flow

Our special Sawtooth Delivery[™] feature prevents material surges for low rates of fertilizer



Accurate.

Easy to operate.

Great spread patte

Heavy duty drive train

Proven PTO drive system and triple speed drives eliminate slipping. Hydraulic drives are standard on the 10 ton model



Optional shredder

Heavy duty blades chop up any clumps and gives a smoother flow of material onto the spinners.



Standard tail lights

Light kit increases visibility and safety.



1-800-843-8731 StoltzfusSpreaders.com



All Stoltzfus Wet Lime Spreaders can be configured with hydraulic drives. Your choice of manual controls or Variable Rate Ready (compatible with most controllers).

Upgrade to Variable Rate Technology for better utilization of valuable nutrient inputs.

Popular options

- Self-contained PTO hydraulic drives
- PTO mechanical spinners
- Hydraulic body chain (plug to tractor)
- Variable Rate Ready (compatible with most controllers)
- Spring Suspension (4-8 ton)
- Flotation tires
- Lights
- Tarp & bow

- Roll top tarp
- Cor-Ten® steel hopper
- 304 Stainless steel hopper
- Brakes
- Shredder (breaks up large clumps before they hit the spinners)
- Special wheel tracks
- Single axle
- 1000 RPM PTO
- Corner pockets (for sideboards)



Optional self contained PTO Hydraulic option with oversized oil tank.



Variable Rate Ready option (compatible with most controllers).

STOLTZFUS LIME SPREADER SPECIFICATIONS						
Models	20	40	50	50F	80	100
Max. load	2 tons	4 tons	5 ton	5 tons	8 tons	10 tons
Hopper volume	53 cu.ft.	84 cu.ft.	103 cu.ft.	177 cu.ft.	177 cu.ft.	212 cu.ft.
Hopper length	78 in.	120 in.	96 in.	120 in.	120 in.	143 in.
Hopper width	60 in.	60 in.	74 in.	78 in.	78 in.	78 in.
Hopper depth	31 in.	31 in.	41 in	45 in.	50 in.	50 in.
Overall length	15 ft.	18 ft.	16 ft.	18 ft.	18 ft.	20 ft.
Overall width	75 in.	75 in.	75 in.	78 in.	94 in.	102 in.
Overall height	65 in.	65 in.	75 in.	79 in.	87 in.	89 in.
Axles	1	2	2	2	2	2
Wheel track (center)	64 in.	64 in.	64 in.	64 in.	75 in.	80 in.
Standard tires	11L x 15 8 ply	19L x 16.1 10 ply	21.5L x 16.1 14 ply			
Weight	2,100 lbs.	2,800 lbs.	2,750 lbs.	3,400 lbs.	4,300 lbs.	5,200 lbs.



1-800-843-8731

StoltzfusSpreaders.com Morgantown, PA 19543

Dealer information: